

MITSUBISHI MSHA-APPROVED ENGINES

Updated: 8/15/2015

Approval Number	Manufacturer	Model	HP @ RPM at 1000ft Elevation	HP	CFM/HP	Ventilation Rate CFM	Particulate Index CFM	DPM grams/hr weighted	DPM grams/hp- hr weighted	Filter Eff. for 5.0 grams/hr	Filter Eff. for 2.5 grams/hr	Date Issued	EPA Compliant per 72.502-1	Exhaust BP Max Limit, in.H2O
7E-B018	MITSUBISHI	S4S-DT	93 @ 2500	93	37.63	3500	9000	14.82	0.29	66	83	4/18/08	Y	48
07-ENA070006	MITSUBISHI	S4S-Y365DP/67DP/68DP	63 @ 2500	63	39.68	2500	4000	6.53	0.2	23	62	5/30/12	Y	27
07-ENA130007	MITSUBISHI	S4S-DT	74 @ 2500	74	40.54	3000	4000	6.14	0.16	19	59	4/18/08	Y	60
7E-B052	MITSUBISHI	S4Q2-Y265DP	48.3 @ 2500	48.3	41.41	2000	4500	6.93	0.27	28	64	11/22/04	Y	26
7E-B099-1	MITSUBISHI	S4S-DT	83 @ 2500	83	42.17	3500	7000	11.49	0.24	56	78	4/18/08	Y	60
07-ENA070004	MITSUBISHI	S4S-Y3DT65DP/67DP/68DP	83 @ 2500	83	42.17	3500	8000	13.18	0.29	62	81	5/30/12	Y	60
07-ENA070002	MITSUBISHI	S4S-DT	93 @ 2500	93	43.01	4000	8000	13.08	0.24	62	81	7/10/07	Y	60
7E-B050	MITSUBISHI	S4S-DT	77 @ 2500	77	45.45	3500	4500	6.91	0.18	28	64	4/22/05	Y	32
07-ENA040004-1	MITSUBISHI	S4S-DT	74 @ 2500	74	47.30	3500	5000	7.75	0.18	35	68	7/10/07	Y	60
07-ENA040007	MITSUBISHI	S4S	63 @ 2500	63	47.62	3000	4500	7.65	0.26	35	67	10/22/03	Y	41
07-ENA040007-1	MITSUBISHI	S4S-DT	83 @ 2500	83	48.19	4000	6500	10.3	0.22	51	76	7/10/07	Y	60
7E-B011	MITSUBISHI	S3L2-Y361 DPA	28 @ 3000	28	53.57	1500	1500	1.98	0.13	0	0	11/21/11	Y	27
7E-B013	MITSUBISHI	S3L2-Y361 DPH	28 @ 3000	28	53.57	1500	1500	1.98	0.13	0	0	11/21/11	Y	27
7E-B057	MITSUBISHI	3044C-T	80.5 @ 2600	80.5	55.90	4500	4500	7.12	0.17	30	65	6/2/05	Y	60
7E-B062	MITSUBISHI	3044C-T	71 @ 2600	71	56.34	4000	5000	8.44	0.23	41	70	6/2/05	Y	60