POWER GENERATION G-Drive CURSOR 13


SPECIFICATIONS

Certification			Stage V - Tier 4 Final
No. of cylinders			6L
Injection System			ECR
Air Intake			TAA
Displacement	liters		8.7
Exhaust System			HI-eSCR2
Stand-by Power @ 1500 rpm		kWm	378
Prime Power @ 1500 rpm		kWm	342
Stand-by Power @ 1800 rpm		kWm	426
Prime Power @ 1800 rpm		kWm	385
Code			C13TEVP03.A39

WEIGHT AND DIMENSIONS

Dimensions (L x W x H)	mm	2281 x 1223 x 1454
Dry Weight	Kg	1399

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

Do you want to know more?

Air Handling

TC (Turbocharged)

NA (Naturally Aspirated)

LEGEND

TCA (Turbocharged with aftercooler)

Injection System

M (Mechanical) ECR (Electronic Common Rail) EUI (Electronic Unit Injector) MPI (Multi Point Injection)

MORE INFORMATION ABOUT CONFIGURATIONS AND ACCESSORIES AVAILABILITY, THROUGH THE WORLDWIDE FPT INDUSTRIAL DISTRIBUTORS NEYWORK

NOT ALL MODELS, STANDARD EQUIPMENT AND ACCESSORIES ARE AVAILABLE IN ALL COUNTRIES. SPECIFICATIONS AND OPTIONS MAY CHANGE WITHOUT NOTICE





Arrangement

V (90° "V" configuration)

L (in line)