3-DRIVE

POWER GENERATION G-Drive CURSOR 16

CURSOR 16
557 kWm @ 1500 rpm

Unregulated

SPECIFICATIONS

Certification			Unregulated
No. of cylinders			6L
Injection System			ECR
Air Intake			TAA
Displacement	liters		15.9
Exhaust System			-
Stand-by Power @ 1500 rpm		kWm	557
Prime Power @ 1500 rpm		kWm	505
Stand-by Power @ 1800 rpm		kWm	578
Prime Power @ 1800 rpm		kWm	523
Code			CURSOR16TE1

WEIGHT AND DIMENSIONS

Dimensions (L x W x H)	mm	2353 x 1114 x 1605
Dry Weight	Kg	1450

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

Do you want to know more?

LEGEND

Arrangement L (in line)

V (90° "V" configuration)

Air Handling

TC (Turbocharged)

NA (Naturally Aspirated)

TCA (Turbocharged with aftercooler)

Injection System

M (Mechanical)

ECR (Electronic Common Rail)

EUI (Electronic Unit Injector)

MPI (Multi Point Injection)

MORE INFORMATION ABOUT CONFIGURATIONS AND ACCESSORIES AVAILABILITY, THROUGH THE WORLDWIDE FPT INDUSTRIAL DISTRIBUTORS NEYWORK

NOT ALL MODELS, STANDARD EQUIPMENT AND ACCESSORIES ARE AVAILABLE IN ALL COUNTRIES. SPECIFICATIONS AND OPTIONS MAY CHANGE WITHOUT NOTICE



