POWER GENERATION G-Drive F36

SPECIFICATIONS

Certification			Stage V - Tier 4 Final
No. of cylinders			4L
Injection System			ECR
Air Intake			TAA
Displacement	liters		3.6
Exhaust System			HI-eSCR2
Stand-by Power @ 1500 rpm		kWm	92
Prime Power @ 1500 rpm		kWm	92
Stand-by Power @ 1800 rpm		kWm	100
Prime Power @ 1800 rpm		kWm	100
Code			F36ETVP03.A94

WEIGHT AND DIMENSIONS

Dimensions (L x W x H)	mm	1111 x 689 x 1050
Dry Weight	Kg	450

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

Do you want to know more?

Air Handling

TC (Turbocharged)

NA (Naturally Aspirated)

LEGEND

TCA (Turbocharged with aftercooler)

Injection System

M (Mechanical) ECR (Electronic Common Rail) EUI (Electronic Unit Injector) MPI (Multi Point Injection)

MORE INFORMATION ABOUT CONFIGURATIONS AND ACCESSORIES AVAILABILITY, THROUGH THE WORLDWIDE FPT INDUSTRIAL DISTRIBUTORS NEYWORK

NOT ALL MODELS, STANDARD EQUIPMENT AND ACCESSORIES ARE AVAILABLE IN ALL COUNTRIES. SPECIFICATIONS AND OPTIONS MAY CHANGE WITHOUT NOTICE



Arrangement

V (90° "V" configuration)

L (in line)